BV - HFO ISO 8217

Fioul lourd 700 Cst – 15 février 2026

En février 2026, le laboratoire indépendant et accrédité Bureau Veritas a analysé un échantillon de fioul lourd HFO 700 amélioré avec la **Technologie des Enzymes XBEE**. L'analyse démontre que ce carburant pour les moteurs HFO/IFO 700 est en conformité avec la norme ISO 8217:2017.

Conclusions :

Les essais ont été réalisés après incorporation d'une dose volumétrique de 1/4000 de l'additif XBEE suivie, d'une période de conservation de l'échantillon à température constante de deux semaines. L'échantillon additivé par la technologie XBEE est conforme aux limites fixées par les spécifications techniques du carburant marine RMG 700 de la norme ISO 8217:2017.

Analyses	Normes	Avec XBEE	Sans XBEE	Unités	Limites
Densité à 15°C	ASTM D 4052	956.8	956.8	kg/m³	991.00 max
Résidu de carbone MCC	ASTM D 4530	11.9	11.9	% (m/m)	18.00 max
Viscosité à 50°C	ASTM D 445	633.9	646.9	mm²/s	-
Point éclair	ASTM D 93	>110.0	>110.0	°C	60 min
Soufre	EN ISO 8754	1.84	1.83	% (m/m)	1.50 max
Cendres	ASTM D 482	0.039	0.062	% (m/m)	0.10 max
Teneur en eau	ASTM D 95	<0.05	0.05	% vol	0.50 max
Point d'écoulement	ASTM D 97	+24	+24	°C	30 max
Acidité	ASTM D 664	0.10	0.10	mgKOH/g	2.5 max
Sulfure d'hydrogène (H2S)	IP 570-Proc. A	<0.60	<0.60	mg/kg	2.00 max
CCAI	Ref. Annex F	813	813	cotation	870.00 max
Sédiments totaux par filtration	ISO 10307-2	0.01	0.02	% (m/m)	0.10 max
Aluminium (Al) + Silicone (Sl)	IP 501	<15	<15	mg/kg	60 max
Sodium (Na)	IP 501	40	38	mg/kg	100 max
Calcium (Ca)	IP 501	3	3	mg/kg	30 max
Zinc (Zn)	IP 501	18	17	mg/kg	15 max
Vanadium (Va)	IP 501	97	102	mg/kg	350 max
Phosphore	IP 501	3	<1	mg/kg	15 max

Annexes

Rapports originaux

Bureau Veritas Commodities Antwerp NV
Romeynsweel 14
2030 Antwerp
Belgium

T: +32 (0)3 546 08 88
E: labco@bureauveritas.com
commodities.bureauveritas.com

Certificate of Analysis

Our ref	**BEANT-25-11573-XXV1999882**	Asset	**Submitted Sample**
Location	**Not specified**	Seals	**None**
Product	**HFO 700**	Packed	**Plastic**
Reference id	**XBEE**	Submitted by	**Ourselves**
Sample received	**13-02-2026**	End of analysis	**15-02-2026**
Subject	**Submitted samples**		
Sample from	**Sample as received**		

Test	Method	Unit	Result
Density at 15 °C (a)	ASTM D4052	kg/m^3	956.8
Micro Carbon Residue	ASTM D4530	% m/m	11.9
Viscosity at 50 °C (a)	ASTM D445	mm^2/s	633.9
Flash Point PM - Proc. B (a)	ASTM D93	Deg C	>110
Sulphur (EDF) (a)	EN ISO 8754	% m/m	1.84
Ash Content	ASTM D482	% m/m	0.039
Water by Distillation	ASTM D95	% v/v	<0.05
Pour Point	ASTM D97	Deg C	24
Acid number	ASTM D664	mg KOH/g	0.10
Hydrogen Sulphide	IP 570 - Proc. A	mg/kg	<0.60
CCAI	ref Annex F		813
Total Sediments - Potential	ISO 10307-2	% m/m	0.01
Metals	IP 501	-	-
Vanadium (V) - ICP	-	mg/kg	97
Sodium (Na) - ICP	-	mg/kg	40
Aluminium (Al) - ICP	-	mg/kg	5
Silicon (Si) - ICP	-	mg/kg	<10
Aluminium + Silicon (Al+Si)	-	mg/kg	<15
ULO metals content (a)	-	-	free of
_Zinc (Zn) - ICP	-	mg/kg	18
_Phosphorus (P) - ICP	-	mg/kg	<1
_Calcium (Ca) - ICP	-	mg/kg	3

Unless specified, the latest version at our disposal of the test methods has been used.
The results relate only to the items tested.

AUTHORIZATION

Dario D'Heldt (Shiftleader)

Certified to ISO 9001
Trade Register Antwerp 333.309
VAT nr. BE 0465.326.123

All tests marked by (a) are accredited by BELAC ref. 486-TEST ISO/IEC 17025

All services are rendered in accordance with Bureau Veritas's General Terms and Conditions of Business, available on request or at https://commodities.bureauveritas.com/general-conditions-of-service.
Laboratory Measurement Uncertainties are not taken into account for the evaluation of specification limits. If product is outside method scope; precision and accuracy of result cannot be guaranteed.

Method Validation data is available upon request.

Bureau Veritas Commodities Antwerp NV
Romeynsweel 14
2030 Antwerp
Belgium

T: +32 (0)3 546 08 88
E: labco@bureauveritas.com
commodities.bureauveritas.com

Certificate of Analysis

Our ref	**BEANT-25-11573-XXV1999882**	Asset	**Submitted Sample**
Location	**Not specified**	Seals	**None**
Product	**HFO 700**	Packed	**Plastic**
Reference id	**XBEE**	Submitted by	**Ourselves**
Sample received	**13-02-2026**	End of analysis	**15-02-2026**
Subject	**Submitted samples**		
Sample from	**Sample as received**		

AUTHORIZATION

Dario D'Heldt (Shiftleader)

Certified to ISO 9001
Trade Register Antwerp 333.309
VAT nr. BE 0465.326.123

All tests marked by (a)
are accredited by
BELAC ref. 486-TEST
ISO/IEC 17025

All services are rendered in accordance with Bureau Veritas's General Terms and Conditions of Business, available on request or at https://commodities.bureauveritas.com/general-conditions-of-service.. Laboratory Measurement Uncertainties are not taken into account for the evaluation of specification limits. If product is outside method scope; precision and accuracy of result cannot be guaranteed.

Method Validation data is available upon request.

Bureau Veritas Commodities Antwerp NV
Romeynsweel 14
2030 Antwerp
Belgium

T: +32 (0)3 546 08 88
E: labco@bureauveritas.com
commodities.bureauveritas.com

Certificate of Analysis

Our ref	**BEANT-25-11573-XXV1999884**	Asset	**Submitted Sample**
Location	**Not specified**	Seals	**None**
Product	**HFO 700 with XBEE additive**	Packed	**Plastic**
Reference id	**XBEE**	Submitted by	**Ourselves**
Sample received	**13-02-2026**	End of analysis	**13-03-2026**
Subject	**Submitted samples**		
Sample from	**Sample as received**		

Test	Method	Unit	Result
Density at 15 °C (a)	ASTM D4052	kg/m^3	956.8
Micro Carbon Residue	ASTM D4530	% m/m	11.9
Viscosity at 50 °C (a)	ASTM D445	mm^2/s	646.9
Flash Point PM - Proc. B (a)	ASTM D93	Deg C	>110.0
Sulphur (EDF) (a)	EN ISO 8754	% m/m	1.83
Ash Content	ASTM D482	% m/m	0.062
Water by Distillation	ASTM D95	% v/v	0.05
Pour Point	ASTM D97	Deg C	24
Acid number	ASTM D664	mg KOH/g	0.10
Hydrogen Sulphide	IP 570 - Proc. A	mg/kg	<0.60
CCAI	ref Annex F		813
Total Sediments - Potential	ISO 10307-2	% m/m	0.02
Metals	IP 501	-	-
Vanadium (V) - ICP	-	mg/kg	102
Sodium (Na) - ICP	-	mg/kg	38
Aluminium (Al) - ICP	-	mg/kg	<5
Silicon (Si) - ICP	-	mg/kg	<10
Aluminium + Silicon (Al+Si)	-	mg/kg	<15
ULO metals content (a)	-	-	free of
_Zinc (Zn) - ICP	-	mg/kg	17
_Phosphorus (P) - ICP	-	mg/kg	<1
_Calcium (Ca) - ICP	-	mg/kg	3

Unless specified, the latest version at our disposal of the test methods has been used.
The results relate only to the items tested.

AUTHORIZATION

Jonathan Van Hecke (Lab Shiftleader)

Certified to ISO 9001
Trade Register Antwerp 333.309
VAT nr. BE 0465.326.123

All tests marked by (a) are accredited by BELAC ref. 486-TEST ISO/IEC 17025

All services are rendered in accordance with Bureau Veritas's General Terms and Conditions of Business, available on request or at https://commodities.bureauveritas.com/general-conditions-of-service.. Laboratory Measurement Uncertainties are not taken into account for the evaluation of specification limits. If product is outside method scope; precision and accuracy of result cannot be guaranteed.

Method Validation data is available upon request.

Bureau Veritas Commodities Antwerp NV
Romeynsweel 14
2030 Antwerp
Belgium

T: +32 (0)3 546 08 88
E: labco@bureauveritas.com
commodities.bureauveritas.com

Certificate of Analysis

Our ref	**BEANT-25-11573-XXV1999884**	Asset	**Submitted Sample**
Location	**Not specified**	Seals	**None**
Product	**HFO 700 with XBEE additive**	Packed	**Plastic**
Reference id	**XBEE**	Submitted by	**Ourselves**
Sample received	**13-02-2026**	End of analysis	**13-03-2026**
Subject	**Submitted samples**		
Sample from	**Sample as received**		

Remarks:

Testing was performed after laboratory hand-blend at 1/4000 Xbee additive doping rate by volume, followed by a two week retention period at constant temperature. The tested sample, blended with Xbee technology meets the specification limits according to the ISO 8217:2017 standard after the retention period.

Revision v.XXV1999884.13032026.1724 due to additional remark.

AUTHORIZATION

Jonathan Van Hecke (Lab Shiftleader)

Certified to ISO 9001
Trade Register Antwerp 333.309
VAT nr. BE 0465.326.123

All tests marked by (a) are accredited by BELAC ref. 486-TEST ISO/IEC 17025

All services are rendered in accordance with Bureau Veritas's General Terms and Conditions of Business, available on request or at https://commodities.bureauveritas.com/general-conditions-of-service.. Laboratory Measurement Uncertainties are not taken into account for the evaluation of specification limits. If product is outside method scope; precision and accuracy of result cannot be guaranteed.

Method Validation data is available upon request.